

Independent Resurvey of the Second Standard Parallel South,
Along the South Boundary of T. 8 S., R. 64 E.

Chains

S C
T8S R64E
S31 | S32

1952

No auxiliary accessory.

From this corner, the original standard cor. of secs. 31 and 32, which is monumented with an unmarked lava stone, 4x10x18 ins., set and witnessed as described in the official record, bears N. 43° 45' W., 2.78 chs. dist. I remove this old corner stone and bury it alongside the above iron post, and destroy all visible evidence of the old corner position and its accessories.

Land, mountainous.

Soil, clay, gravel, and rock.

Timber, scattered juniper; undergrowth, sagebrush and greasewood.

N. 89° 59' W., along the S. bdy. of sec. 31, along a rhumb line.

Over mountainous land, through scattered timber and undergrowth; desc. 310 ft. over W. and NW. slopes.

17.60 Ravine, drains S. 10° E.; asc. 20 ft. over gradual E. slope.

22.10 Spur, slopes S. 10° E.; desc. 60 ft. over W. slope.

28.30 Ravine, drains S.; asc. 25 ft. over gradual E. slope.

32.10 Spur, slopes S.; desc. 100 ft. over SW. slope.

40.00 Point for the standard $\frac{1}{4}$ sec. cor. of sec. 31.

Using the original iron post, which is 3 ft. long, 1 in. diam., I set it 10 ins. in the ground to bedrock, and supported in a mound of stone, 3 $\frac{1}{2}$ ft. base, 26 ins. high, with brass cap mkd.

S C
 $\frac{1}{4}$ S 31

1952

~~1911~~

No auxiliary accessory.

From this corner, the point for the original standard $\frac{1}{4}$ sec. cor. of sec. 31, from which I removed the above iron post, bears N. 51° 32' W., 3.30 chs. dist. I destroy all visible evidence of the old corner position and its accessories.

Desc. 110 ft. over SW. slope.

56.00 Foot of slope, bears NW. and SE.; thence over nearly level desert.

80.00 Point for the standard cor. of Ts. 8 S., Rs. 63 and 64 E.

Using the original iron post, which is 3 ft. long, 3 ins. diam., I set it 30 ins. in the ground, surrounded with a flat mound of stone, 2 ft. diam., with brass cap mkd.