

284

Dependent Resurvey, East $\frac{1}{2}$ Mile, S. Bdy. of T. 8 S., R. 66 E.,
Along the Second Standard Parallel South

Chains

Reestablishment of the Line Established by
A. R. Talamantes, U. S. Surveyor, under Group 1, Nevada, in 1911.

Beginning at the standard cor. of T. 8 S., Rs. 66 and 67 E., which is monumented with an iron post, 3 ins. diam., 12 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

N. $89^{\circ} 50'$ W., along the S. bdy. of sec. 36. (E. $\frac{1}{2}$ mile)

Over gently rolling desert land, through light undergrowth.

24.14 The original closing cor. of Ts. 9 S., Rs. 66 and 67 E., which is monumented with an iron post, 3 ins. diam., 10 ins. above ground, firmly set, mkd. and witnessed as described in the official record.

35.50 Dry wash, in ravine, 1.50 chs. wide, 5 ft. deep, course SE.

40.08 The original standard $\frac{1}{4}$ sec. cor. of sec. 36, which is monumented with a trachyte stone, 6x6x18 ins., set 12 ins. in ground, mkd. $\frac{1}{4}$ on N. face and SC on top face, and witnessed by a small mound of stone N. of cor.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

S C
 $\frac{1}{4}$ S 36

1952

Bury the old corner stone alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, N. of cor.

Land, gently rolling desert.

Soil, sand and gravel, with scattered boulders.

Timber, none; undergrowth, sagebrush, greasewood, and cacti.

Independent Resurvey, West $5\frac{1}{2}$ Miles, S. Bdy. of T. 8 S., R. 66 E.,
Along the Second Standard Parallel South

Superseding the Original Survey Executed by
A. R. Talamantes, U. S. Surveyor, under Group 11, Nevada, in 1911.

From the reestablished standard $\frac{1}{4}$ sec. cor. of sec. 36, T. 8 S., R. 66 E., hereinbefore described.

N. $89^{\circ} 59'$ W., along the S. bdy. of sec. 36 (W. $\frac{1}{2}$ mile), along a rhumb line.

Over very gently rolling desert, through light undergrowth.

39.92 Point for the standard cor. of secs. 35 and 36, at 80.00 chs. westing from the SE. cor. of the township.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 6 ins. in the ground to solid rock, supported in a mound of stone, $4\frac{1}{2}$ ft. base, 24 ins. high, with brass cap mkd.