

Independent Resurvey, Portion of the S. Bdy., T. 8 S., R. 66 E.,
Along the Second Standard Parallel South

Chains

78.70

Small flat spur, slopes SE.

80.00

Point for the standard cor. of secs. 31 and 32.

Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground to bedrock, and in a mound of stone, 4½ ft. base, 12 ins. high, with brass cap mkd.

S C
T8S R66E
S31 | S32

1952

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

From this corner, the original standard cor. of secs. 31 and 32, which is monumented with a trachyte stone, 6x12x18 ins., lying loose on the ground, mkd. as described in the official record, bears N. 24° 10' E., 0.81 chs. dist. I bury this old corner stone alongside the above iron post.

Land, mountainous.

Soil, rock, sand, and clay.

Timber, very scattering juniper; undergrowth, sagebrush, greasewood, and cacti.

N. 89° 59' W., along the S. bdy. of sec. 31, along a rhumb line.

Over mountainous land, through very scattering undergrowth; desc. 105 ft. over W. slope.

4.00

Gulch, drains SW. for 3 chs., then turns S.; asc. 145 ft. over E. slope.

16.00

Divide, ridge, bears S. 40° W. and N. 40° E. for 1 ch., then turns to N.; desc. 215 ft. over W. slope.

24.00

Head of gully, drains NW.; thence along N. slope.

31.40

Rocky spur, slopes N.; desc. 335 ft. over rocky W. slope.

40.00

Point for the standard ¼ sec. cor. of sec. 31.

Set an iron post, 30 ins. long, 2½ ins. diam., 16 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base, 13 ins. high, with brass cap mkd.

S C
¼ S 31

1952

Raise a mound of stone, 3 ft. base, 1½ ft. high, N. of cor.

There is no remaining evidence of the original corner.

Desc. 65 ft. over W. slope.

45.00

Rocky gulch, drains N.; asc. 75 ft. over E. slope.