

305

Independent Resurvey of the Second Standard Parallel South,  
Along the South Boundary of T. 8 S., R. 65 E.

Chains	
76.10	Dim unimproved road, bears N. 5° W., and S. 5° E.
80.00	Point for the standard cor. of secs. 31 and 32.  Using the original iron post, which is 3 ft. long, 3 ins. diam., I set it 24 ins. in the ground to underlying rock, with brass cap mkd.  <div>S C T8S R65E S31   S32</div> <div>1952 <del>1911</del></div> Raise a supporting mound of stone, 3 ft. base, 1 ft. high, around the iron post, and raise an auxiliary mound of stone, 4 ft. base, 2½ ft. high, N. of cor.  From this corner, the point for the original standard cor. of secs. 31 and 32, from which I removed the above iron post, bears N. 38° 10' W., 2.28 chs. dist. I destroy all visible evidence of the old corner position and its accessories.  Land, nearly level desert. Soil, sandy clay loam. Timber, none; undergrowth, sagebrush, greasewood, and cacti.
	N. 89° 59' W., along the S. bdy. of sec. 31, along a rhumb line. Over nearly level desert, through medium dense undergrowth.
9.40	Leave nearly level desert; asc. 80 ft. over E. slope.
16.00	Crest of round topped hill; desc. 40 ft. over W. slope.
23.00	Wash, 8 lks. wide, drains S. 70° E.; asc. 100 ft. over rolling E. slope.
40.00	Point for the standard ¼ sec. cor. of sec. 31.  Using the original iron post, which is 3 ft. long, 1 in. diam., I set it 30 ins. in the ground, with brass cap mkd.  <div>S C ¼ S 31</div> <div>1952 <del>1911</del></div> Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor.  From this corner, the point for the original standard ¼ sec. cor. of sec. 31, from which I removed the above iron post, bears N. 36° 28' W., 2.40 chs. dist. I destroy all visible evidence of this old corner position and its accessories.  Asc. 570 ft. over mountainous land, over a NE. slope.
71.40	Spur, slopes N.; desc. 250 ft. over W. slope.