

## Dependent Resurvey, Portion of the South Bdy. of T. 19 S., R. 60 E.

Chains	<p>Land, nearly level. Soil, gravelly. Timber, none; undergrowth, creosote brush.</p>
	<p>S. 88° 52' W., bet. secs. 6 and 31.</p> <p>Over nearly level land; asc. 77 ft. to <math>\frac{1}{4}</math> sec. cor.</p>
34.20	Unimproved road, bears N. 55° E. and S. 55° W.
39.08	<p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 22 ins. in the ground, with brass cap mkd.</p> $\frac{1}{4} \frac{S31}{S 6}$ <p>1956</p>
	<p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 2 ft. high, N. of cor.</p>
42.20	Unimproved road, bears N. 30° E. and S. 30° W.
63.20	Same road, bears S. 80° E. and N. 80° W.
78.47	<p>The cor. of Ts. 19 and 20 S., Rs. 59 and 60 E., mkd. by a limestone, 8x6x4 ins., mkd. with 6 notches on three sides and set in a mound of stone.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 20 ins. in the ground, with brass cap mkd.</p> $\begin{array}{c} T19S \\ R59E R60E \\ \hline S36   S31 \\ \hline S 1   S 6 \\ T20S \\ 1956 \end{array}$ <p>Set the cor. stone in hole alongside the iron post and raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 2<math>\frac{1}{2}</math> ft. high, W. of cor.</p> <p>Land, nearly level. Soil, gravelly. Timber, none; undergrowth, creosote brush.</p>
Dependent Resurvey of the West Boundary of T. 19 S., R. 60 E.	
Reestablishment of the Survey Executed by Brunt and Proctor in 1881.	
	<p>N. 0° 09' E., bet. secs. 31 and 36.</p> <p>Over nearly level desert land; asc. 27 ft. to <math>\frac{1}{4}</math> sec. cor.</p>
1.40	Unimproved road, bears NE. and S. 30° W.; another unimproved road enters from east.
30.70	Road, improved, gravelled, bears E. and N. 75° W.