Dependent Resurvey of a Portion of the N. Bdy., T. 20 S., R. 60 E.

Chains	
	Thence
	N. 88° 04' W., bet. secs. 4 and 33.
	Over nearly level desert valley, through scattered vegetation, along unimproved roadway.
10.00	Leave unimproved roadway, bears N. 75° W. and E.
21.01	Point for the E. 1/16 sec. cor. of secs. 4 and 33, at proportionate dist., cor. not monumented.
42.02	Point for the ¼ sec. cor. of secs. 4 and 33, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T19S R60E ¼ S33 / S 4 T20S 1957
	Raise a mound of stone, 2 ft. base, 1½ ft. high, N. of cor.
63.03	Point for the W. 1/16 sec. cor. of secs. 4 and 33, at proportionate dist., cor. not monumented.
84.04	The cor. of secs. 4, 5, 32 and 33, which is monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the official record of the dependent resurvey of a portion of the S. bdy. of T. 19 S., R. 60 E., executed concurrently under this same group.
	Land, nearly level desert valley. Soil, sandy and gravelly clay loam. Vegetation, scattered yucca and creosote bush.

Dependent Resurvey of a Portion of the Subdivision, T. 20 S., R. 60 E.

Reestablishment of the survey executed
by Woods and Myrick, Deputy Surveyors, in 1882

Beginning at the point for cor. of secs. 26, 27, 34 and 35, which is monumented with a mesquite stake, 2x2x18 ins. above ground, of local origin, but believed to be a perpetuation of the original cor. point.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T20S R60E
S27 | S26
S34 | S35
1957

Thence

N. 0° 10' W., bet. secs. 26 and 27.

Over nearly level desert valley land, through scattered vegetation.