

Dependent Resurvey, East Boundary, T. 20 S., R. 60 E.

N. 0° 05' W., bet. secs. 31 and 36. (N. half mile).

Over gently rolling desert land.

9.95 Wash, 8 lks. wide, course E.

40.13 The cor. of secs. 25, 30, 31 and 36, marked by a local survey monument, a concrete block, 6 x 6 x 14 ins. long, firmly set, with nail in top. This is a local restoration established in 1929 and is recorded in Clark County records in Plat Book No. 1, Page 96. It is accepted as being the best available evidence of the position of the original corner.

At the corner point

Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.

T20S
R60E R61E
S25|S30
S36|S31
1952

Dig a circular trench, 5 ft. diam., and raise a mound of stone around the post to top, and bury the local concrete monument alongside the iron post.

Land, gently rolling desert.
Soil, sandy and gravelly, 4th rate.
Timber, none; undergrowth, sage and greasewood.

Dependent Resurvey of Subdivision of T. 20 S., R. 60 E.

Reestablishment of the Survey Executed
by J. E. Woods and W. H. Myrick, Deputy
Surveyors in 1882

From the cor. of secs. 25, 30, 31 and 36, on E. bdy.
of Tp.