5 E	Dependent Resurvey, Portion of the Subdivision of T. 21 S., R. 60 E.
Chains	S 1/16 S 9 S 10 1955
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
39.97	The ½ sec. cor. of secs. 9 and 10, identified and restored by Cartographer Lewis in 1954, who found the corner point marked by a limestone, marked with ½ on the W. face, firmly set and surrounded by a low mound of stone, where he
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
	S 9 S 10
* 1	1954
*	Bury the old corner stone alongside the iron post.
	N. 0° 12' E., beginning new measurement.
*	Over gently rolling land, through sparse undergrowth.
19.985	Point for the N. 1/16 sec. cor. of secs. 9 and 10, at proportionate distance.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.
۳	N 1/16 S 9 S 10 1955
	Raise a mound of stone, 3 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.
32.15	Dry wash, 50 lks. wide, 10 ft. deep, course E.
39.97	The cor. of secs. 3, 4, 9 and 10, marked by an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the record of the 1952 resurvey of a portion of T. 21 S., R. 60 E.
*	Land, rolling. Soil, sand and gravel. Vegetation, scattered creosote bush, salt brush, and cactus.
-	From the cor. of secs. 4, 5, 32 and 33, on the S. bdy. of the township, marked by an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., set, mkd. and witnessed as described in the record of the 1955 resurvey of T. 22 S., R. 60 E.
	N. 0° 36' E., bet. secs. 32 and 33.
	Over rolling land, through sparse undergrowth.
14.20	Dry wash, 30 lks. wide, 3 ft. deep, course N. 30° E.
20.462	Point for the S. 1/16 sec. cor. of secs. 32 and 33, at proportionate distance.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, and in a mound of stone to top, with brass cap mkd.