

DEPENDENT RESURVEY OF A PORTION OF EAST BDY., T. 22 S., R. 60 E.

Chains	
	<p>Reestablishment of Surveys Executed by Deputy Surveyors Brunt and Proctor, in 1881.</p> <hr/>
	<p>Beginning at the cor. of Ts. 22 and 23 S., Rs. 60 and 61 E., marked by an iron post restored by Cartographer Lewis, in 1954, who found the corner point marked by a limestone, 18 x 12 x 7 ins., marked with 6 grooves on all four faces, firmly set in a mound of stone, where he</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 22 ins. in the ground with brass cap mkd.</p> <div><div>T 22 S</div><div>R 60 E R 61 E</div><div>S 36 S 31</div><div>S 1 S 6</div><div>T 23 S</div><div>1954</div></div> <p>Bury the old corner stone alongside the iron post.</p> <p>North, between secs. 31 and 36.</p> <p>Over level land, through sparse vegetation.</p>
20.085	<p>Point for the S. 1/16 sec. cor. of secs. 31 and 36, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div><div>S 1/16</div><div>S 36 S 31</div><div>1955</div></div> <p>Raise a mound of stone, 3 ft. base, 2$\frac{1}{2}$ ft. high, W. of cor.</p>
40.17	<p>The $\frac{1}{4}$ sec. cor. of secs. 31 and 36, identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a limestone, 12 x 10 x 5 ins., marked $\frac{1}{4}$ on west face, firmly set in old mound of gravel, where he</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div><div>$\frac{1}{4}$</div><div>S 36 S 31</div><div>1954</div></div> <p>Bury the old corner stone alongside the iron post.</p> <hr/>
19.69	<p>N. 1° 40' E., beginning new measurement.</p> <p>Point for the N. 1/16 sec. cor. of secs. 31 and 36, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2$\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div><div>N 1/16</div><div>S 36 S 31</div><div>1955</div></div>