

DEPENDENT RESURVEY OF NORTH BOUNDARY, T. 22 S., R. 60 E.

Chains	
	Reestablishment of Surveys Executed by by Brunt and Proctor, in 1881.
	Beginning at the cor. of Ts. 21 and 22 S., Rs. 60 and 61 E., marked by an iron post, firmly set, marked and witnessed as described in the official record of the survey of T. 22 S., R. 61 E., the plat of which bears approval date of February 18, 1953.
	S. 86° 20' W., bet. secs. 1 and 36.
	Over gently rolling land, through scattered undergrowth.
3.50	Dry wash, 30 lks. wide, 10 ft. deep, course N. 45° E.
18.41	Point for the E. 1/16 sec. cor. of secs. 1 and 36. at proportionate distance. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd. <div>E 1/16 $\frac{S\ 36}{S\ 1}$ 1955</div>
36.82	Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd. <div>¼ $\frac{S\ 36}{S\ 1}$ 1955</div>
55.23	Raise a low mound of stone around the iron post and deposit a lime- stone rock, 5 x 3 x 3 ins., mkd. X, alongside. Point for the W. 1/16 sec. cor. of secs. 1 and 36, at proportionate distance. Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd. <div>W 1/16 $\frac{S\ 36}{S\ 1}$ 1955</div>
73.64	Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. The cor. of secs. 1, 2, 35 and 36, identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a sandy limestone, 12 x 10 x 6 ins., marked with 5 grooves on W. and 1 groove on E. face, firmly set and surrounded by a low mound of stone, where he Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd. <div>T 21 S R 60 E S 35 S 36 S 2 S 1 T 22 S 1954</div>