DEPENDENT RESURVEY OF THE NORTH BOUNDARY, T. 22 S., R. 60 E. Chains Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. 41.105 Point for the 4 sec. cor. of secs. 6 and 31, at proportionate distance; there is no remaining evidence of the original corner. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd. S 31 S 6 1955 Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. 42.30 Unimproved road, winds northwesterly.and southerly. 61.658 Point for the W. 1/16 sec. cor. of secs. 6 and 31, at proportionate distance. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd. W 1/16 S 31 S 6 Raise a mound of stone, 3 ft. base, 3 ft. high, N. of cor. The cor. of Ts. 21 and 22 S., Rs. 59 and 60 E., identified and restored by Cartographer Lewis in 1954 who found the corner point 80.45 marked by a limestone, $24 \times 12 \times 6$ ins., marked with 6 grooves on all four edges, firmly set and surrounded by a low mound of stone, Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd. T 21 S R 59 E R 60 E S 36 | S 31 S1 | S6 T 22 S 1954 Bury the old corner stone alongside the iron post.

Land, rolling. Soil, gravelly.

Vegetation, creosote bush and salt brush.

Dependent Resurvey of the South Boundary, T. 22 S., R. 60 E.

Reestablishment of the Survey Executed by Brunt and Proctor, Deputy Surveyors, in 1881.

Beginning at the cor. of Ts. 22 and 23 S., Rs. 60 and 61 E., identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a limestone, $18 \times 12 \times 7$ ins., marked with 6 grooves on all 4 sides, firmly set and surrounded by a low mound of stone, where he

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground with brass cap mkd.