

304

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 22 S., R. 60 E.

Chains	<div>N 1/16 S 12 S 7 1955</div> <p>from which</p> <p>A mine tunnel, bears W., 500 lks. dist.</p> <p>Raise a mound of stone, 3 ft. base, 3 ft. high, W. of cor.</p> <p>82.34 The cor. of secs. 1, 6, 7 and 12, identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a limestone, 18 x 10 x 3 ins., marked with 5 grooves on S. and 1 groove on N. face, firmly set and surrounded by a low mound of stone, where he</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 18 ins. in the ground and in a mound of stone to top, with brass cap mkd.</p> <div>T 22 S R 59 E R 60 E S 1 S 6 SS 12 S 7 1954</div> <p>Bury the old corner stone alongside the iron post.</p> <p>Land, rolling and rough. Soil, rocky and gravelly. Vegetation, creosote bush, salt brush, and cactus.</p>
1.00	<p>N. 0° 30' W., bet. secs. 1 and 6.</p> <p>Over rough rolling land, through scattered undergrowth.</p> <p>Ascend W. slope of hill, which bears NW.</p>
11.00	<p>Top of ascent; descend N. slope.</p>
19.745	<p>Point for the witness S. 1/16 sec. cor. of secs. 1 and 6.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 5 ins. in the ground and in a mound of stone to top, with brass cap mkd.</p> <div>W C S 1/16 S 1 S 6 1955</div>
19.895	<p>True point for the S. 1/16 sec. cor. of secs. 1 and 6, at proportionate distance. Falls on rocky outcrop, impractical for monument.</p>
29.80	<p>Base of descent, bears NW.</p>
39.79	<p>The ¼ sec. cor. of secs. 1 and 6, identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a limestone, 18 x 14 x 3 ins., marked with ¼ on W. face, firmly set and surrounded by a low mound of stone, where he</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div>¼ S 1 S 6 1955</div> <p>Bury the old corner stone alongside the iron post.</p>