

DEPENDENT RESURVEY OF THE WEST BOUNDARY, T. 22 S., R. 60 E.

Chains	N. 0° 29' W., beginning new measurement.
20.525	<p>Point for the N. 1/16 sec. cor. of secs. 1 and 6, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground with brass cap mkd.</p> <div>N 1/16 S 1   S 6 1955</div> <p>Raise a mound of stone, 3 ft. base, 3 ft. high. W. of cor.</p>
41.05	<p>The cor. of Ts. 21 and 22 S., Rs. 59 and 60 E., identified and restored by Cartographer Lewis in 1954 who found the corner point marked by a limestone, 24 x 12 x 6 ins., marked with 6 grooves on all four faces, firmly set and surrounded by a low mound of stone, where he</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam.. 24 ins. in the ground with brass cap mkd.</p> <div>T 21 S R 59 E   R 60 E S 36   S 31 S 1   S 6 T 22 S 1954</div> <p>Bury the old corner stone alongside the iron post.</p> <p>Land, rough and rolling. Soil, sandy and rocky. Vegetation, creosote bush, salt brush, and cactus.</p>
Dependent Resurvey of Subdivisional Lines with Establishment of 1/16 Section Corners, T. 22 S., R. 60 E.	
Reestablishment of Surveys Executed by Brunt and Proctor in 1881.	
	<p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 28' W., bet. secs. 35 and 36.</p> <p>Over rolling land, through scattered undergrowth.</p>
2.10	Dry wash, 70 lks. wide, 12 ft. deep, course N. 40° E.; ascend hill.
19.935	<p>Point for the S. 1/16 sec. cor. of secs. 35 and 36, at proportionate distance.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 14 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p> <div>S 1/16 S 35   S 36 1955</div>
20.00	Top of ascent; descend N. slope.
25.10	Base of descent, also unimproved road, bears E. and W.