

Dependent Resurvey of a Portion of the Subdivision, T. 21 S., R. 61 E.

Chains	
20.87	<p>Point for the E. 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T21S R61E E 1/16 $\frac{S18}{S19}$ 1957</p>
41.74	<p>Point for the ¼ sec. cor. of secs. 18 and 19, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground to bedrock, and in a mound of stone, with brass cap mkd.</p> <p style="text-align: center;">T21S R61E ¼ $\frac{S18}{S19}$ 1957</p>
58.35	<p>Telephone line, paralleling road, bears N. 20° W. and S. 20° E.</p>
62.61	<p>Point for the W. 1/16 sec. cor. of secs. 18 and 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R61E W 1/16 $\frac{S18}{S19}$ 1957</p>
80.46	<p>The cor. of secs. 13, 18, 19 and 24, monumented by an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the field notes of the dependent resurvey of T. 21 S., R. 60 E., executed in 1955.</p> <p>Land, rolling. Soil, sand and gravel. Timber, none; undergrowth, creosote bush, mesquite and salt brush.</p>
Subdivision of Section 19, T. 21 S., R. 61 E.	
20.135	<p>From the ¼ sec. cor. of secs. 19 and 30.</p> <p>N. 0° 40' W., on the N.-S. center line of sec. 19.</p> <p>Point for the center S. 1/16 sec. cor. of sec. 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 12 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.</p> <p style="text-align: center;">T21S R61E C S 1/16 S19 C 1957</p>
32.00	<p>Wash, 4 ft. deep, 1 ch. wide, drains N. 15° E. and SW</p>
40.27	<p>Point for the center ¼ sec. cor. of sec. 19, at the intersection of the E.-W. center line of sec. 19.</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, and in a mound of stone to top, with brass cap mkd.</p>