

Resurvey of a Portion of the W. Bdy. of T.21S.,R.61E.

Chains	
49.16	Shallow wash, 50 lks. wide, course N.70°E.
52.56	Dirt road, bears NW. and SE.
60.12	Point for the N 1/16 sec. cor. of secs. 7 and 12, at proportionate distance. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd. N 1/16 S 12 S 7 1952 Dig a circular trench, 4 ft. diam., and raise a mound of earth and stone around the post to top. Deposit three green wine bottles alongside the iron post.
62.56	Well travelled dirt road, bears NE. and SW.
80.16	The cor. of secs. 1, 6, 7 and 12 marked with the original monument, a limestone 10x8x4 ins., marked with 5 grooves on S. and 1 groove on N. face, set alongside a local monument, a concrete cylinder 6 ins. diam., 12 ins. long, buried flush with surface of ground, with aluminum cap mkd. T 21 S S 1 S 6 S 12 S 7 R60E R61E R E 196 Add the marks: U S B L M 1952. Dig a circular trench, 3 ft. diam., and riase a flat mound of stone around the corner monument. From the corner An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground for a reference monument, bears S.88°48'W., 50 lks. dist., with brass cap mkd. T21S R60E S 1 S 12 R M 1952 and an arrow pointing to the true corner. Land, gently rolling desert. Soil, sandy and gravelly, 4th rate. Timber, none; undergrowth, greasewood and catclaw.
	N. 0° 07' W., bet. secs. 1 and 6. (South half mile.) Over gently rolling desert land.
13.20	Small wash, course E.
19.93	Point for the S 1/16 sec. cor. of secs. 1 and 6, at proportionate dist. Set an iron post, 3 ft. long, 2 ins. diam., 28 ins. in the ground, with brass cap mkd. S 1/16 S 1 S 6 1952