

Resurvey of a Portion of the W. Bdy. of T.21S.,R.61E.

Chains	
	Dig a circular trench, 3 ft. diam., and raise a mound of stone around post to top.
20.66	Wash, 50 lks. wide, course N. 70° E.
28.36	Wash, 40 lks. wide, course NE.
29.895	Point for the N-S 1/64 sec. cor. of secs. 1 and 6, at proportionate dist.
	Set a redwood post, 2 x 4 x 30 ins. long, 25 ins. in the ground, mkd. S 1/64 on N., S 1 on W., and S 6 on E. face.
36.06	Dirt road, bears N. 32° E., and S. 32° W.
39.86	The 1/4 sec. cor. of secs. 1 and 6, marked with the original monument, a limestone, 12 x 12 x 8 ins., mkd. 1/4 on W. face, set alongside a local monument, a concrete cylinder, 6 ins. diam., 12 ins. long, buried flush with surface, with aluminum cap mkd.
	T21S R60E R61E S 1 S 6 RE 196
	Add the marks: U S B L M 1952.
	From the corner,
	An iron post, 3 ft. long, 2 ins. diam., set 27 ins. in the ground for a reference monument bears N. 89° 52' W., 50 lks. dist., with brass cap mkd. 1/4 S 1 R M 1952 and an arrow pointing to the true corner.
	<hr style="width: 10%; margin: 0 auto;"/> N. 2° 07' E., bet. secs. 1 and 6. (North half mile) Over gently rolling desert land.
28.50	Dirt road, bears E. and W.
33.70	Wash, 30 lks. wide, course S. 70° E.
40.16	Middle of Charleston Road, bears E. and W.
40.46	Intersect the Fifth Standard Parallel South on the S. bdy. of sec. 36, T. 20 S., R. 60 E.
	Point for the closing corner of Tps. 21 S., Rs. 60 and 61 E., at proportionate dist.
	Set an iron post, 3 ft. long, 2 ins. diam., 26 ins. in the ground, with brass cap mkd.
	T20S R60E S36 <hr style="width: 10%; margin: 0 auto;"/> S 1 S 6 R60E R61E T21S CC 1952
	from which