

Resurvey of a Portion of the W. Bdy., T.21S., R.61E.

Chains

A U.S.C. and G.S. triangulation station, "PIT", bears S.33°40'E., 93 lks. dist., a concrete block, 10x10x8 ins. above ground, with brass cap mkd. U S C & G S PIT. The published latitude is 36°09' 32.341" N., and longitude is 115°12' 24.693" W.

A U.S.C. and G.S. reference monument, bears N.75°07'E., 53.8 links dist., a concrete block, 10x10x2 ins. above ground, with brass cap mkd. PIT No. 1 and an arrow pointing to PIT station.

The standard cor. of Tps. 20 S., Rs. 60 and 61 E., bears S.89°33'E., 9.09 chs. dist.

Land, gently rolling desert.
Soil, sandy and gravelly, 4th rate.
Timber, none; undergrowth, sage and greasewood.

Dependent resurvey of the Subdivisions of T.21S., R.61E.

Reestablishment of the Surveys executed by
J.M. Brunt and W.H. Proctor in 1881.

From the cor. of secs. 19, 24, 25 and 30 on the E. bdy. of the Tp., marked by an iron post, 2 ins. diam., set 14 ins. below the surface of paved "Bond Road", with brass cap mkd. and witnessed as described in the official 1943 resurvey record of the resurvey of the W. bdy. of T. 21 S., R. 62 E.

from which

A concrete monument, 6 ins. diam., set flush with surface of the ground for a reference monument by Clark County, bears N.45°35'E., 66.2 lks. dist., with brass cap mkd.

CLARK COUNTY
T21S
R61E R62E
S24 | S19
S25 | S30
Witness 1
RE 209
NEVADA

A concrete monument, 6 ins. diam., set flush with surface of the ground for a reference monument by Clark County, bears S.45°40'E., 63.9 lks. dist., with brass cap mkd.

CLARK COUNTY
T21S
R61E R62E
S24 | S19
S25 | S30
Witness 4
RE 209
NEVADA

A concrete monument, 6 ins. diam., set flush with surface of the ground for a reference monument by Clark County, bears S.44°39'W., 64.3 lks. dist., with brass cap mkd.