

## Subdivision of Sec. 24, T.21S., R.61E.

Chains	
	From the $\frac{1}{4}$ sec. cor. of secs. 24 and 25.
	N. $0^{\circ} 28'$ E., on the N-S center line of sec. 24.
	Over gently rolling desert land.
.22	N. edge of pavement on Bond Road, bears N. $89^{\circ} 39'$ E., and S. $89^{\circ} 37'$ W.
.50	Main telephone line, parallel to road.
20.565	Point for the C-S $1/16$ cor. of secs. 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \\ \text{S } 1/16 \quad   \quad \text{S } 24 \\ \text{C} \\ 1952 \end{array}$
	Dig a circular trench, 4 ft. diam., and raise a mound of earth around the post to top.
36.00	West end of small sand dune, bears NE.
41.13	Point for the C $\frac{1}{4}$ cor. of sec. 24, at the intersection with the E-W center line of sec. 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C } \frac{1}{4} \text{ S } 24 \\ 1952 \end{array}$
	Dig a circular trench, 4 ft. diam., and raise a mound of earth around the post to top.
48.75	Wash, 60 lks. wide, course N. $60^{\circ}$ E.
56.75	Side wash, 20 lks. wide course NE.
61.895	Point for the C-N $1/16$ cor. of sec. 24.
	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 28 ins. in the ground, with brass cap mkd.
	$\begin{array}{c} \text{C} \\ \text{N } 1/16 \quad   \quad \text{S } 24 \\ \text{C} \\ 1952 \end{array}$
	Dig a circular trench, 4 ft. diam., and raise a mound of earth around the post to top.
76.00	Enter wash, on right bank, 20 ft. high, course N. $60^{\circ}$ E.
82.30	Leave wash, on left bank, 6 ft. high, course N. $60^{\circ}$ E.
82.66	The $\frac{1}{4}$ sec. cor. of secs. 13 and 24.
	Land, gently rolling.
	Soil, sandy and gravelly, 4th rate.
	Timber, scattering mesquite in washes; undergrowth, burro brush and Mormon tea.