

## Dependent Resurvey, S. Bdy., T. 22 S., R. 61 E.

<p>Chains</p> <p>29.50</p> <p>39.90</p> <p>40.15</p>	<p>Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">W 1/16 <math>\frac{S\ 33}{S\ 4}</math> 1952</p> <p>Dig a circular trench, 3 ft. diam., and raise a mound of stone, around the post to top.</p> <p>Wash, 35 lks. wide, course N.</p> <p>E. edge of pavement on State Highway No. 91-466, bears N.0°27'E. to Las Vegas and S.0°27'W. to Los Angeles.</p> <p>The cor. of secs. 4, 5, 32, and 33, marked by an iron bolt set flush with the pavement on the center line of the highway. This cor. is the restoration of the original corner by the Nevada State Highway Department and is recorded in their official records, dating back to 1925. From the iron bolt, the highway reference monuments:</p> <p>A concrete block, 6 x 6 x 10 ins. above ground, bears S.89°33'E., 40 ft. dist., mkd. N.</p> <p>A concrete block, 6 x 6 x 10 ins. above ground, bears N.89°33'W., 40 ft. dist., mkd. N.</p> <p>And new reference monuments:</p> <p>An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears N.45°E., 100 lks. dist., with brass cap mkd. T22S R61E S33 RM 1952 and an arrow pointing to the true cor.</p> <p>An iron post, 3 ft. long, 2 ins. diam., set 28 ins. in the ground, for a reference monument, bears S.45°E., 100 lks. dist., with brass cap mkd. T23S R61E S4 RM 1952 and an arrow pointing to the true cor.</p> <p>Land, gently rolling desert. Soil, sandy and gravelly, 3rd rate. Timber, none; undergrowth, greasewood and sage.</p>
	<p style="text-align: center;">Dependent Resurvey of a Portion of the North Boundary of T.22S., R.61E., M.D.M.</p>
	<p>The cor. of secs. 1, 2, 35 and 36 is marked by a wooden fence post, 10 x 8 ins., 5 ft. high, with fences extending E. and S. This position is recognized as the correct corner by adjacent land owners and is recorded in the Clark County records in File 1, Page 19, R.P.E. surveys. It is accepted as the best existing evidence of the position of the original corner.</p> <p>At the corner point, at NW. cor. of fence post,</p> <p>Set an iron post, 30 ins. long, 2½ ins. diam., 26 ins. in the ground, with brass cap mkd.</p> <p style="text-align: center;">T21S R61E S 35   S 36 S 2   S 1 T22S 1952</p>