Dependent Resurvey, N. Bdy., T. 22 S., R. 61 E.

	Chains	
	9.807	Point for the E-W 1/64 sec. cor. of secs. 5 and 32 at proportionate dist.
		Set a redwood post, 2 x 4 x 30 ins., 20 ins. in the ground mkd. E-W 1/64 on W., S 5 on S., and S 32 on N. face.
	19.615	Point for the W 1/16 sec. cor. of secs. 5 and 32, at proportionate dist.
	9 and	Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 30 ins. in the ground, with brass cap mkd.
		$W 1/16 \frac{s}{s} \frac{32}{5}$
		1952
		Dig a circular trench, 3 ft. diam., and raise a mound of stone around the post to top.
	29.422	Point for the W-W 1/64 sec. cor. of secs. 5 and 32, at proportionate dist.
		Set a redwood post, 2 x 4 x 30 ins., 20 ins. in the ground, mkd. W-W 1/64 on W., S 5 on S. and S 32 on N. face.
	30.00	Center of wash, 40 lks. wide, course N. 35° E.
	30.50	Gravel bank, 6 ft. high, bears N. 35° E. and S. 35° W.; leave eroded valley. Over rolling desert land.
The second secon	39.23	The cor. of secs. 5, 6, 31 and 32, marked by a fir stake, 2 x 2 x 10 ins. above ground, set in small stone mound, mkd. S32 on NE., R61E S5 on SE., T22S S6 on SW. and S31 on NW. face and a metal tag mkd. RE 6. This is a local establishment, recorded in Clark County records and is well related to original cors. to the N. and W. It is accepted as the best available evidence of the position of the original cor.
	× × * 1	At the corner point
		Set an iron post, 3 ft. long, 2 ins. diam., 30 ins. in the ground, with brass cap mkd.
		T21S R61E S31 S32 S 6 S 5 T22S
		Dig a circular trench, 5 ft. diam., and raise a mound of stone around the post to top.
		Land, rolling and eroded desert land. No improvements. Soil, sandy and gravelly, 4th rate. Timber, none; undergrowth, sagebrush and greasewood.
-		S. 89° 56' W., bet. secs. 6 and 31.
		Over rolling desert land, with a few sand dunes.
-	20.615	Point for the E 1/16 sec. cor. of secs. 6 and 31 at proportionate dist.
1		