

Dependent Resurvey of East Two and a Half Miles of South Boundary,
T. 43 N., R. 36 E.

| Chains | <p style="text-align: center;">Reestablishment of the Survey Executed by Deputy Surveyor O. A. Palmer in 1868.</p> |
|--------|---|
| | <p>Beginning at the cor. of Ts. 42 and 43 N., Rs. 36 and 37 E., which is marked by an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the field notes of the 1954 resurvey of T. 42 N., R. 37 E.</p> |
| | <p>N. 89° 41' W., bet. secs. 1 and 36.</p> |
| | <p>Over nearly level land.</p> |
| 40.06 | <p>Point for the ¼ sec. cor. of secs. 1 and 36, at proportionate distance; there is no remaining evidence of the original corner.</p> |
| | <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | $\begin{array}{r} \frac{1}{4} \text{ S } 36 \\ \text{ S } 1 \\ 1954 \end{array}$ |
| | <p>Bury an igneous stone, 5x5x2 ins. mkd. X, alongside the iron post.</p> |
| 80.12 | <p>Point for the cor. of secs. 1, 2, 35 and 36, at proportionate distance; there is no remaining evidence of original corner.</p> |
| | <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | $\begin{array}{r} \text{T43N R36E} \\ \text{S35 S36} \\ \text{S2 S1} \\ \text{T42N} \\ 1954 \end{array}$ |
| | <p>Bury an igneous stone, 4x3x1 ins., mkd. X, alongside the iron post.</p> |
| | <p>Land, nearly level.</p> |
| | <p>Soil, alkaline loam.</p> |
| | <p>Vegetation, greasewood and sagebrush.</p> |
| | <p>No timber.</p> |
| | <p>N. 89° 41' W., bet. secs. 2 and 35.</p> |
| | <p>Over nearly level land.</p> |
| 40.06 | <p>Point for the ¼ sec. cor. of secs. 2 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> |
| | <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.</p> |
| | $\begin{array}{r} \frac{1}{4} \text{ S } 35 \\ \text{ S } 2 \\ 1954 \end{array}$ |
| | <p>Bury an igneous stone, 5x4x2 ins. mkd. X, alongside the iron post.</p> |
| 80.12 | <p>Point for the cor. of secs. 2, 3, 34 and 35, at proportionate distance; there is no remaining evidence of the original corner.</p> |
| | <p>Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with the brass cap mkd.</p> |