

## Dependent Resurvey of the East Boundary of T. 42 N., R. 37 E.

Chains	
	<p style="text-align: center;">Reestablishment of the Survey Executed by Deputy Surveyor O. A. Palmer, in 1868.</p> <hr style="width: 20%; margin: auto;"/> <p>Beginning at the cor. of Ts. 41 and 42 N., R. 37 E., on the W. bdy. of T. 41 N., R. 38 E., marked by an iron post, firmly set, marked and witnessed as described in the official record of the survey of the latter township, the plat of which bears approval date of January 23, 1915.</p> <p>N. 0° 19' E., bet. sec. 36, T. 42 N., R. 37 E., and sec. 6, T. 41 N., R. 38 E.</p> <p>Over mountainous land.</p>
5.92	<p>The closing cor. of Ts. 41 and 42 N., R. 38 E., found marked with an iron post, 3 ins. diam., firmly set, marked and witnessed as described in the official record of the survey of T. 41 N., R. 38 E., executed by Haigh and Harris in 1913 under Group 9, Nevada.</p> <p>Thence bet. secs. 31 and 36, Ts. 42 N., Rs. 37 and 38 E., continuing measurement.</p> <p>Note: The original corners in advance along this line will no longer serve for sections of T. 42 N., R. 38 E.</p>
11.10	Spur, slopes NW.; descend 635 ft. over rocky NE. slope.
39.385	<p>Point for the E. <math>\frac{1}{4}</math> sec. cor. of sec. 36, at proportionate distance; there is no remaining evidence of the original corner. This corner is now remonumented to refer to sec. 36 only.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> <math>\frac{1}{4}</math>  S36    1954 </div> <p>Raise a low mound of stone around the iron post and deposit an igneous stone, 10x4x2 ins., mkd. X, alongside.</p>
43.75	Buffalo Creek, an intermittent stream in a bed 40 lks. wide, drains N. 70° W.; ascend 215 ft. over stony SW. slope.
58.75	Rocky spur, slopes W.; descend 230 ft. over NW. slope.
78.77	<p>The cor. of secs. 25, 30, 31 and 36, marked by the original monument, a slate stone, 16x8x6 ins., marked with 5 grooves on N. and 1 groove on S. face, firmly set and surrounded by a low mound of stone. This cor. is now remonumented to refer to secs. 25 and 36 only.</p> <p>At the corner point.</p> <p>Set an iron post, 30 ins. long, 2<math>\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center;"> T42N  R37E R38E  S25    S36    1954 </div> <p>Raise a mound of stone, 2<math>\frac{1}{2}</math> ft. base, 1<math>\frac{1}{2}</math> ft. high, W. of cor., and deposit an igneous stone, 5x4x4 ins., mkd. X, alongside the iron post, with the original cornerstone alongside.</p>