

Dependent Resurvey of a Portion of the Subdivision, T. 45 N., R. 37 E.

Chains

T45N R37E.

$$\frac{1}{4} \frac{S 3}{S 10}$$

1956

Deposit broken glass at base of post.

Over rolling land; asc. 80 ft.

80.10 The cor. of secs. 3 and 10.

Land, level to rolling.

Soil, sandy.

Timber, none; undergrowth, rye grass, greasewood, and sagebrush.

N. 2° 04' W., along the W. bdy. of sec. 3.

Over rolling land, through heavy undergrowth; asc. gentle SE. slope 10 ft.

2.66 Point for the closing cor. of secs. 4 and 9, hereinafter described; asc. 80 ft.

39.78 Point for the $\frac{1}{4}$ sec. cor. of secs. 3 and 4, at proportionate dist.; there is no remaining evidence of the original corner.

As this corner will no longer serve for sec. 4, I reestablish it to refer to sec. 3 only, as follows.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 20 ins. in the ground, with brass cap mkd.

T45N R37E

$$\frac{1}{4} \frac{S 3}{S 3}$$

1956

Raise a mound of stone, 2 $\frac{1}{2}$ ft. base, 2 ft. high, to E.

Continue bearing and distance along the W. bdy. of sec. 3; asc. 20 ft. along SE. slope.

42.69 Point for the $\frac{1}{4}$ sec. cor. of sec. 4, hereinafter described; asc. 310 ft.

77.15 Top of slope; desc. 20 ft. down NE. slope.

81.06 Intersect the Ninth Standard Parallel North at record dist., W. of the standard cor. of secs. 33 and 34.

Point for the closing cor. of secs. 3 and 4.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 4 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T46N R37E

$$\frac{S 4 | S 3}{T45N R37E}$$

C C

1956