

230

Survey of a Portion of the Subdivision, T. 45 N., R. 37 E.

Chains

Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.

T45N
R36E R37E

S 1 | S 6 C
 | S 7 C

1956

Raise a mound of stone, 5 ft. base, 3 ft. high, to E.

From this cor., the cor. of secs. 1 and 12, T. 45 N., R. 36 E., which is monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as previously described, bears S. 0° 02' E., 88 lks. dist.

Land, hilly.

Soil, sandy loam, volcanic outcroppings.

Timber, none; undergrowth, sagebrush.

At the point for the W. ¼ sec. cor. of sec. 6, on the W. bdy. of the township, 40.00 chs. northing from the closing cor. of secs. 6 and 7.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base to top, with brass cap mkd.

T45N R37E

¼
| S 6

1956

From this cor., the ¼ sec. cor. of sec. 1, T. 45 N., R. 36 E., which is monumented with an iron post, 2½ ins. diam., set, mkd. and witnessed as previously described, bears S. 0° 02' E., 95 lks. dist.

From the cor. of secs. 5, 6, 7 and 8.

N. 0° 01' W., bet. secs. 5 and 6.

Over hilly land, through moderate undergrowth; asc. 40 ft. along SSW slope.

31.90 Wash, 4 lks. wide, 6 ins. deep, drains SW.; asc. 210 ft. along SW. slope to cor.

40.00 The ¼ sec. cor. of secs. 5 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to bedrock, and in a mound of stone, 4 ft. base to top, with brass cap mkd.

T45N R37E

¼
S 6 | S 5

1956

Continue along SW. slope; asc. 90 ft.

50.00 Slope changes to NW. slope; desc. 140 ft.

59.50 Wash, 4 lks. wide, 6 ins. deep, drains W.; asc. 250 ft. along SW. slope.

79.63 Intersect the Ninth Standard Parallel North.