

302

## Dependent Resurvey of the East Boundary, T. 45 N., R. 38 E.

Chains

N. 0° 25' E., beginning new measurement.

Over gently rolling land, through light sagebrush.

4.50 Dry wash, drains S. 80° W.

15.00 Dry wash, drains N. 40° W.

18.40 Wash, 25 lks. wide, seasonal flow, course S. 35° W.; asc. 40 ft. over S. slope.

21.00 Spur, slopes W.

40.99 The cor. of secs. 1, 6, 7 and 12, monumented by a basalt stone, 3x5x10 ins., firmly set in a mound of stone, mkd. with 5 grooves on S. and 6 grooves on E. faces.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T45N	
R38E R39E	
S 1   S 6	
S12   S 7	
1957	

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, rolling.

Soil, gravelly and sandy loam.

Undergrowth, sagebrush.

N. 0° 23' E., along the E. bdy. of sec. 1.

Over gently rolling land, through medium sagebrush.

3.30 Dry wash, drains N. 45° W.; asc. 20 ft. over SW. slope.

10.40 Spur, slopes W.; desc. 15 ft. over NE. slope.

17.10 Dry wash, drains S. 80° W.

25.30 Dry wash, drains W.

32.80 Dry wash, drains N. 80° W.

40.63 The ¼ sec. cor. of sec. 1, monumented by a basalt stone, 12x6x3 ins., firmly set and mkd. ¼ on W. face.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T45N	
¼	
S 1   S 6	
1957	

Bury the original corner stone alongside the iron post.

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

N. 0° 26' E., beginning new measurement.