

## Dependent Resurvey of the East Boundary, T. 45 N., R. 38 E.

Chains	Desc. 60 ft. over N. slope, through medium sagebrush.
16.00	Dry wash, drains W.; asc. 20 ft. over broken S. slope.
23.00	Top of ascent; desc. 20 ft. over NW. slope.
37.20	Dry wash, drains W.; asc. 60 ft. over SW. slope.
41.88	The closing cor. of Ts. 45 N., Rs. 38 and 39 E. on the 9th Standard Parallel North, monumented by a basalt stone, 14x10x9, firmly set with wood post in a mound of stone.
	At the corner stone.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground, with brass cap mkd.
	T45N R38E S36 S 1   S 6 T45N C.C. 1957
	Bury the original corner stone alongside the iron post.
	Raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.
	From this cor., the standard cor. of Ts. 46 N., Rs. 38 and 39 E., bears N. 89° 03' E., 8.64 chs. dist.
	Land, rolling.
	Soil, gravelly loam.
	Undergrowth, medium sagebrush.

## Dependent Resurvey of the Subdivisional Lines, T. 45 N., R. 38 E.

	Reestablishment of the survey executed by Deputy Surveyor O.A. Palmer in 1868 and 1869.
	From the cor. of secs. 35 and 36 on the S. bdy. of the township.
	N. 2° 33' W., bet. secs. 35 and 36, along the E. slope, through medium sagebrush.
14.20	Desc. 120 ft. over NE. slope.
25.30	Dry wash, drains W.; asc. 105 ft. over S. slope.
33.70	Spur, slopes W.; desc. 108 ft. over NE. slope.
40.40	Point for the ½ sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.
	T45N R38E ½ S35   S36 1957
	Desc. 60 ft. over NE. slope.
47.80	Dry wash, 30 lks. wide, course N. 45° W.; asc. 120 ft. over SW. slope.
64.00	Spur, slopes NW.