

Dependent Resurvey of the Subdivisional Lines, T. 45 N., R. 38 E.

Chains

N. 0° 16' W., bet. secs. 2 and 3.

Over nearly level ground, through heavy sagebrush.

16.30 Dry wash, 25 lks. wide, 2 ft. deep, drains S. 70° W.

35.10 Dry wash, 20 lks. wide, 1 ft. deep, drains W.

38.10 Small spur, slopes W.

40.25 Point for the 1/4 sec. cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T45N R38E

1/4
S 3 | S 2
1957

41.15 Dry wash, 20 lks. wide, 1 ft. deep, drains S. 30° W.

44.75 Unimproved road, bears N. 45° E. and S. 45° W.

75.10 Dry wash, drains W.; asc. 20 ft. over S. slope.

82.18 Intersect the 9th Standard Parallel North.

Point for the closing cor. of secs. 2 and 3, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T46N R38E

S34
S 3 | S 2
T45N R38E
C C
1957

From the point of intersection, the standard cor. of secs. 34 and 35, T. 46 N., R. 38 E., bears N. 89° 03' E., 8.15 chs. dist.

Land, rolling.
Soil, sandy loam.
Undergrowth, sagebrush.

The point for the N. 1/4 sec. cor. of sec. 2 is at midpoint on the N. bdy. of the sec.

Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 2
T45N R38E
1957

From this cor., the standard 1/4 sec. cor. of sec. 35, T. 46 N., R. 38 E., bears N. 89° 03' E., 8.18 chs. dist.