

346

Dependent Resurvey of the West Boundary, T. 46 N., R. 38 E.

Chains

Reestablishment of the survey made by O. A. Palmer in 1869.

The cor. of T. 46 N., R. 37, and 38 E., is monumented with a 2½ ins. iron post, set, mkd. and witnessed as described in the official record of T. 45 N., R. 37 E.

N. 0° 41' W., on the W. bdy. of sec. 31.

Over sagebrush flat.

3.70

Barbed wire fence bears E. and W., thence over flat reseeded area.

40.36

Point for ¼ sec. cor. of secs. 31 and 36, at proportionate dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T46N
R37E R38E

¼
S36|S31
1957

80.72

The cor. of secs. 25, 30, 31 and 36, mkd. by a porphyry stone 18x9x6 ins., firmly set, with 6 grooves on E. face.

At the cor. point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T46N
R37E R38E

S25|S30
S36|S31
1957

Bury original cornerstone alongside the iron post.

Land, flat.

Soil, sandy loam.

Vegetation, crested wheat grass, mustard and sagebrush.

N. 0° 51' W., bet. secs. 25 and 30.

Over sagebrush flat.

18.40

Wash, 20 lks. wide, 5 ft. deep, drains S. 60° W.

28.00

Wash, 25 lks. wide, 4½ ft. deep, drains S. 55° W.

40.45

The ¼ sec. cor. of secs. 25 and 30, mkd. by a porphyry rock 10x8x6 ins., firmly set, with ¼ chiseled on S. face.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T46N
R37E R38E

¼
S25|S30
1957

Bury the original cornerstone alongside the iron post.