

Dependent Resurvey of the West Boundary, T. 46 N., R. 38 E.

Chains	
	T46N R37E R38E 1/4 S12 S 7 1957
48.10	Ditch, 30 lks. wide, 12 ft. deep, drains S. 60° W.
49.80	Barbed wire fence, bears N. 20° E. and S. 20° W.
60.00	Wash, 20 lks. wide, 4 ft. deep, drains S. 30° W.
65.40	Wash, 25 lks. wide, drains S. 35° W.
68.70	Quinn River, 3 chs. wide, 10 ft. deep, drains S. 30° W.
80.72	The cor. of secs. 1, 6, 7 and 12, mkd. by a porphyry stone 20x10x8 ins., firmly set, with 6 grooves on the E. face and 5 grooves on the S. face. At the cor. point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T46N R37E R38E S 1 S 6 S12 S 7 1957 Bury original cornerstone alongside the iron post. Land, meadow. Soil, loam. Vegetation, meadow grass.
	N. 1° 19' W., bet. secs. 1 and 6. Over sagebrush flats.
19.90	Wash, 12 lks. wide, 3 ft. deep, drains S. 15° W.
40.61	The 1/4 sec. cor. of secs. 1 and 6, mkd. by a porphyry stone 12x6x4 ins., firmly set, with 1/4 chisled on S. face. At the cor. point Set an iron post, 30 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd. T46N R37E R38E 1/4 S1 S6 1957 Bury original cornerstone alongside the iron post.
	N. 1° 29' W., beginning new measurement. Over flat country.
40.69	The cor. of Ts. 46 and 47 N., Rs. 37 and 38 E., mkd. by a porphyry stone 14x12x8 ins., firmly set, with 6 grooves on N, S., E. and W. faces. At the cor. point