

Dependent Resurvey of the E. Bdy., T. 47 N., R. 38 E.

Chains																																	
53.10	Unimproved road, bears N. 80° E. and S. 80° W.																																
55.90	Unimproved road, bears E. and W.																																
63.60	Unimproved road, bears N. 20° W. and S. 20° E.																																
70.30	The closing cor. of secs. 6 and 7, T. 47 N., R. 39 E., monumented by a 4x4 in. post, firmly set and mkd. CC on E. face, with metal township plate mkd. cor. sec. 6 and 7.																																
	At the corner point																																
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.																																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T47N</td> <td> </td> <td>T47N</td> <td></td> </tr> <tr> <td>R38E</td> <td> </td> <td>R39E</td> <td></td> </tr> <tr> <td>S12</td> <td> </td> <td>S 6</td> <td>CC</td> </tr> <tr> <td></td> <td> </td> <td>S 7</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1957</td> <td></td> </tr> </table>	T47N		T47N		R38E		R39E		S12		S 6	CC			S 7				1957													
T47N		T47N																															
R38E		R39E																															
S12		S 6	CC																														
		S 7																															
		1957																															
80.36	The cor. of secs. 1 and 12, monumented by a porphyry rock, 24x12x8 ins., firmly set, mkd. with 5 grooves on S. and 1 groove on N. faces.																																
	At the corner point																																
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.																																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>T47N</td> <td> </td> <td>T47N</td> <td></td> </tr> <tr> <td>R38E</td> <td> </td> <td>R39E</td> <td></td> </tr> <tr> <td>S 1</td> <td> </td> <td>S 6</td> <td></td> </tr> <tr> <td>S12</td> <td> </td> <td></td> <td></td> </tr> <tr> <td></td> <td></td> <td>1957</td> <td></td> </tr> </table>	T47N		T47N		R38E		R39E		S 1		S 6		S12						1957													
T47N		T47N																															
R38E		R39E																															
S 1		S 6																															
S12																																	
		1957																															
	Bury the original corner stone alongside the iron post.																																
	Land, nearly level.																																
	Soil, sandy loam.																																
	Vegetation, willows and sagebrush.																																
	N. 0° 22' W., along the E. bdy. of sec. 1.																																
	Over nearly level ground, through heavy sagebrush.																																
12.30	The closing cor. of secs. 1 and 6 on the NW. bdy. of the abandoned McDermitt Military Reservation, mkd. by the original monument, a porphyry rock, 24x4x24 ins., mkd. CC M.R. on N. face.																																
	At the corner point																																
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.																																
	<table style="margin-left: auto; margin-right: auto;"> <tr> <td>CC</td> <td></td> <td></td> <td></td> </tr> <tr> <td>T47N</td> <td></td> <td></td> <td></td> </tr> <tr> <td>R38E</td> <td>R39E</td> <td></td> <td></td> </tr> <tr> <td>S 1</td> <td> </td> <td>S 6</td> <td></td> </tr> <tr> <td></td> <td> </td> <td>R</td> <td></td> </tr> <tr> <td>M</td> <td></td> <td></td> <td></td> </tr> <tr> <td>S 1</td> <td> </td> <td>S 6</td> <td></td> </tr> <tr> <td></td> <td></td> <td>1957</td> <td></td> </tr> </table>	CC				T47N				R38E	R39E			S 1		S 6				R		M				S 1		S 6				1957	
CC																																	
T47N																																	
R38E	R39E																																
S 1		S 6																															
		R																															
M																																	
S 1		S 6																															
		1957																															
	Bury the original corner stone alongside the iron post.																																
	Leave abandoned Military Reservation; thence with the reestablishment of the survey executed by Deputy Surveyor D. Van Lenep in 1878.																																
	Continuing on the same bearing, with continuous measurement.																																
29.30	Unimproved road, bears E. and W.																																
30.97	Point for the ¼ sec. cor. of sec. 6, T. 47 N., R. 39 E., at the cor. of fences bearing N. and W., recognized as the corner by adjacent land owners and is accepted as the best existing evidence of the position of the original corner.																																