

## Subdivision of Section 1, T. 16 N., R. 63 E.

Chains	
1.50	Road, bears NE. and SW.
19.94	Point for the CE 1/16 sec. cor. of sec. 1.  Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           E 1/16            C ————— C            S 1            1956         </div> Deposit broken glass alongside the iron post, 12 ins. below the surface of the ground.
21.00	Wash, 20 lks. wide, 1½ ft. deep, drains SW.
32.50	Road, bears NW. and SE.
39.88	The C ¼ sec. cor. of sec. 1.  <div style="text-align: center;">           _____            N. 89° 42' W., beginning new measurement.         </div>
8.50	Road, bears NE. and SW.
28.20	Wash, 20 lks. wide, 2 ft. deep, drains SW.
39.86	The ¼ sec. cor. of secs. 1 and 2.  Land, nearly level. Soil, sandy and gravelly loam. Timber, none; undergrowth, scattered sagebrush.
	From the CE 1/16 sec. cor. of sec. 1.  N. 0° 16' W., on the N. and S. center line of the NE ¼ of sec. 1.
1.70	Wash, 10 lks. wide, 1½ ft. deep, drains SW.
14.00	Road, bears NE. and SW.
19.96	Point for the NE 1/16 cor. of sec. 1 at the intersection with the E. and W. center line of the NE ¼.  Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.  <div style="text-align: center;">           NE 1/16            S 1            1956         </div> Deposit broken glass alongside the iron post, 12 ins. below the surface of the ground.
23.10	Graded, gravelled road, bears NW. and SE.
39.92	Intersect N. bdy. of the Tp. at the E 1/16 cor. of secs. 1 and 36, monumented with an iron post, 2½ ins. diam., firmly set as defined in the returns for the resurvey of a portion of the S. bdy., T. 17 N., R. 63 E.  <div style="text-align: center;">           _____         </div>