

Dependent Resurvey of 5th Stan, Par. S., along portion of S. Bdy.,
T. 20 S., R. 59 E.

Chains	<p>S C T20S R58E S35 S36 1957</p> <p>Land, gently rolling to slightly broken desert valley. Soil, sandy to gravelly clay loam. Timber, none. Undergrowth, yucca and creosote brush.</p>
	<p>Dependent Resurvey, Portion of the W. Bdy., T. 21 S., R. 59 E.</p>
	<p>Reestablishment of the survey executed by Brunt and Proctor, Deputy Surveyors, in 1881.</p> <p>Beginning at the true point for the cor. of secs. 1, 6, 7 and 12, T. 21 S., Rs. 58 and 59 E., determined by proportionate measurement bet. the original cor. of secs. 7, 12, 13 and 18 and the original 1/4 sec. cor. of secs. 1 and 6; there is no remaining evidence of the original corner. This true point for the corner falls at an unsafe place for cor. of the SW. face of broken cliffs.</p> <p>From the true point for cor.</p> <p>The witness cor. of said secs. 1, 6, 7 and 12, at a safe place on the true line bet. secs. 6 and 7, bears S. 85° 19' E., 1.01 chs. dist., hereinafter described.</p> <p>Also, from the true point for the cor. of secs. 1, 6, 7 and 12. The original cor. of secs. 7, 12, 13 and 18, bears S. 1° 34' E., 79.74 chs. dist., and is monumented with a limestone, 18x18x6 ins., firmly set in a mound of stone and mkd. as described in the official record.</p> <p>At the corner point</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, with the old corner stone deposited alongside the iron post, and in a mound of stone, 2 ft. base, 14 ins. high, with brass cap mkd.</p> <p>T21S R58E R59E S12 S 7 S13 S18 1957</p> <p>Thence, from the true point for cor. of secs. 1, 6, 7 and 12. N. 1° 34' W., bet. secs. 1 and 6.</p> <p>Asc. 350 ft. over steep broken cliffs, facing SW.</p> <p>9.60 Crest of spur ridge, slopes S. 30° E. from N. 30° W.; desc. 240 ft. over broken NE. slope to the S. 1/16 sec. cor.</p> <p>19.935 Point for the S. 1/16 sec. cor. of secs. 1 and 6, at proportionate dist.</p> <p>Set an iron post, 30 ins. long, 2 1/2 ins. diam., 4 ins. in the ground, and in a mound of stone, 3 ft. base, 26 ins. high, with brass cap mkd.</p> <p>T21S R58E R59E S 1/16 S 1 S 6 1957</p>