

Dependent Resurvey, Portion of the W. Bdy., T. 21 S., R. 59 E.

Chains

The standard cor. of T. 20 S., Rs. 58 and 59 E., bears N. 89° 27' E., 7.03 chs. dist.

Ash Creek Spring, in a deep gulch, course S. 75° E. from NW., bears S. 86° 23' W., 31.52 chs. dist.

Land, part mountainous, part desert valley.

Soil, part rocky, part sandy and gravelly clay loam.

Timber, none.

Undergrowth, yucca and creosote brush.

Dependent Resurvey, Portion of the Subdivision, T. 21 S., R. 59 E.

Reestablishment of the survey executed by Brunt and Proctor, Deputy Surveyors, in 1881.

Beginning at the point for cor. of secs. 5, 6, 7 and 8, at proportionate dist.; there is no remaining evidence of the original corner.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T21S R59E

S 6 | S 5

S 7 | S 8

1957

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of corner.

From the corner

The original cor. of secs. 7, 8, 17 and 18 bears S. 1° 36' E., 76.21 chs. dist., and is monumented with a limestone, 14x12x8 ins., firmly set in a mound of stone and mkd. as described in the official record.

At the corner point

Set an iron post, 30 ins. long; 2½ ins. diam., 18 ins. in the ground, with the old corner stone deposited alongside the base, and in a mound of stone to top, with brass cap mkd.

T21S R59E

S 7 | S 8

S 18 | S 17

1957

Also, from the cor. of secs. 5, 6, 7 and 8.

The original ¼ sec. cor. of secs. 5 and 8, bears N. 83° 56' E., 42.12 chs. dist., and is monumented with a limestone, 14x10x8 ins., firmly set in a mound of stone and mkd. as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground, with the old corner stone deposited alongside the base, and in a mound of stone, 3 ft. base to top, with brass cap mkd.

T21S R59E

¼ S 5

S 8

1957

Thence, from the cor. of secs. 5, 6, 7 and 8.

N. 88° 32' W., bet. secs. 6 and 7.