Dependent Resurvey	, Portion	of	the	Subdivision,	т.	21	S.	, R.	59	E.
--------------------	-----------	----	-----	--------------	----	----	----	------	----	----

Chains

20.00 Flat spur, slopes S. 15° E. from N. 1° 43' W.; thence along crest of same; ascending gradually.

23.17 Point for the N. 1/16 sec. cor. of secs. 5 and 6, at proportionate dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 8 ins. in the ground, and in a mound of stone, 3 ft. base, 22 ins. high, with brass cap mkd.

T21S R59E

N 1/16
S 6 | S 5
1957

36.50 Ridge, bears E. and W.; desc. over gentle NNE. slope.

46.18 Intersect the 5th Stan. Par. S. on the S. bdy. of sec. 31, T. 20 S., R. 59 E. at the original closing cor. of secs. 5 and 6, which is monumented with a limestone, 16x8x8 ins. firmly set in a mound of stone, and mkd. as described in the official record.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 12 ins. in the ground, with the old corner stone deposited alongside the base, and in a mound of stone, $2\frac{1}{2}$ ft. base, 18 ins. hihg, with brass cap mkd.

T20S R59E S31 S 6 S 5 C C T21S R59E 1957

From this corner

The standard cor. of secs. 31 and 32, T. 20 S., R. 59 E., bears S. 89° 56' E., 7.99 chs. dist.; hereinbefore described.

Land, nearly level to rolling, hilly desert valley. Soil, sandy and gravelly clay loam. Timber, none.
Undergrowth, yucca and creosote brush.

Survey of a Portion of the Subdivision, T. 21 S., R. 59 E.

A preliminary investigation revealed the fact that the center lines of sec. 6 had been surveyed previously by an engineer who is registered and licensed by the State of Nevada. This was done in connection with the laying out of 40 five-acre tracts, situated in and completely occupying the $E_2^{\downarrow}NW_2^{\downarrow}$, $W_2^{\downarrow}SE_2^{\downarrow}$ and $NE_2^{\downarrow}SW_2^{\downarrow}$ of said sec. 6. The claimants of several of the tracts have already started valuable improvements, whose locations are dependent on this tract layout. In order to maintain the integrity of the various tracts as thus established, the 1/16 and $\frac{1}{4}$ sec. cors. established by the above mentioned registered engineer on the north-south and east-west center lines of sec. 6 are accepted in the present work as having been properly established by the aforementioned registered engineer.

Beginning at the $\frac{1}{4}$ sec. cor. of secs. 6 and 7.

N. 0° 43' W., on north-south center line of sec. 6.