

Survey of a Portion of the Subdivision, T. 21 S., R. 59 E.

Chains

- 62.10 Wash, along foot of slope, drains SSE. from W.
- 65.70 Same wash, drains SW.
- 83.15 Intersect the 5th Stan, Par. S. on the S. bdy. of sec. 31, T. 20 S., R. 59 E. The N. $\frac{1}{4}$ sec. cor. of sec. 6, as established by private engineer, is monumented with a wooden post, 4x4x18 ins. above ground.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a flat mound of stone to top, with brass cap mkd.

$\frac{1}{4}$ S 6

T21S R59E

1957

From which

The standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 20 S., R. 59 E., bears S. 89° 56' E., 8.48 chs. dist., hereinbefore described.

A firmly embedded boulder, 20x20x12 ft. above ground, bears W., 30 lks. dist., mkd. X B0.

Reset the wooden post alongside the iron post and raise a mound of stone, 3 ft. base, 2 ft. high, S. of cor.

Land, rolling desert.

Soil, sandy and gravelly clay loam.

Timber, none.

Undergrowth, yucca and creosote brush.

At the point for the E. 1/16 sec. cor. on the N. bdy. of sec. 6 and at proportionate dist.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 16 ins. in the ground, and with a quart of broken glass at the base, with brass cap mkd.

E 1/16 S6

T21S R59E

1957

From which

The standard $\frac{1}{4}$ sec. cor. of sec. 31, T. 20 S., R. 59 E., bears N. 89° 56' W., 11.87 chs. dist., hereinbefore described.

At the point for the W. 1/16 sec. cor. on the N. bdy. of sec. 6 and at proportionate dist.

Set an iron post, 30 ins. long, 2 $\frac{1}{2}$ ins. diam., 22 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

W 1/16 S6

T21S R59E

1957

From which

The standand cor. of T. 20 S., Rs. 58 and 59 E., bears N. 89° 56' W., 12.40 chs. dist., hereinbefore described.