Dependent Resurvey,	Portion	of	the	Subdivision	of	Т.	20	S.,	R.	59	Ε.

_		
	Chains	
	75.20	Wash, 1 ch. wide, 20 ft. deep, drains S. 85° E.
	82.00	Wash, 1 ch. wide, 15 ft. deep, drains S. 85° E.
	85.845	The cor. of secs. 1, 2, 35 and 36 on the N. bdy. of the township, which is monumented with an iron post, 2½ ins. diam., firmly set, marked and witnessed as described in the official record.
	• • • • • • • • • • • • • • • • • • •	Land; gently rolling desert valley, cut by deep washes. Soil; loam, sand, gravel and rock. Timber; none. Undergrowth; yucca and creosote brush.
		Survey of Subdivision of Section Lines, T. 20 S., R. 59 E.
-		Subdivision of Sec. 1
		From the ½ sec. cor. of secs. 1 and 12.
	***	N. 2° 25'. E., on the N. and S. center line of sec. 1.
		Asc. slightly along a very gradual E. slope, through scattered yucca and creosote brush.
	15.10	Wash, 50 lks. wide, 5 ft. deep, drains E.
	17.10	Wash, 50 lks. wide, 5 ft. deep, drains SE. for 3 chs. to junction with preceding wash.
	20.96	Point for the center S. 1/16 sec. cor. of sec. 1.
200		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 14 ins. in the ground, and in a mound of stone, 2 ft. base, 16 ins. high, with brass cap mkd.
		T20S_R59E
	•	S1/16 S 1
		1957
	26.70	Sandy wash, 2 chs. wide, 10 ft. deep, at junction of washes from W., and N. 50° W., drains S. 80° E.
	31.70	Wash, 50 1ks. wide, 5 ft. deep, drains S. 80° E.
	40.30	Wash, 50 1ks. wide, 10 ft. deep, drains E. from NW.
	41.92	Point for the center & sec. cor. of sec. 1, at the point of intersection with the E. and W. center line.
		Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 18 ins. in the ground and in a mound of stone, 2 ft. base, 12 ins. high, with brass cap mkd.
	•	
		T20S R59E C表 + S1 1957
	44.30	Wash, 30 lks. wide, 3 ft. deep, drains S. 80° E.
	55.10	Wash, 2 chs. wide, 10 ft. deep, drains N. 80° E.