Chains	
	The S. bdy. of sec. 32 was retraced in connection with the survey of the subdivisional lines of sections in T. 23 S., R. 61 E. and is shown in the field notes thereof, concurrently surveyed under Group 364, Nevada.
	From the ¼ sec. cor. of secs. 5 and 32, which is monumented with an iron post, 2½ ins. diam., firmly set, mkd. and witnessed as described in the 1956 resurvey notes.
	N. 2° 42' W., on the N. and S. center line of sec. 32.
20.52	Point for the center S. 1/16 sec. cor. of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	T22S R61E c S 1/16 |S 32 c 1957
41.04	Point for the center ¼ sec. cor. of sec. 32, at the intersection of the E. and W. center line of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone to top, with brass cap mkd.
	T22S R61E C ¼ S 32 1957
61.27	Point for the center N. 1/16 sec. cor. of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, and in a mound of stone to top, with brass cap mkd
	T22S R61E c N 1/16 |S 32 c 1957
81.50	The ¼ sec. cor. of secs. 29 and 32.
	From the ¼ sec. cor. of secs. 32 and 33, which is monumented with an iron post, firmly set, mkd. and witnessed as described in the official record.
	S. 88° 35' W., on the E. and W. center line of sec. 32.
19.22	Point for the center E. 1/16 sec. cor. of sec. 32.
	Set an iron post, 30 ins. long, 2½ ins. diam., 22 ins. in the ground to bedrock, and in a mound of stone to top, with brass cap mkd.
	T22S R61E E 1/16 c----c S 32 1957
38.44	The center ¼ sec. cor. of sec. 32.