

286

Dependent Resurvey of the South and West Boundaries and
a Portion of the Subdivision of T. 23 S., R. 61 E.

Chains

is determined to be Latitude 36° 53' 43" N., Longitude 115° 06' 00.7" W. The mean magnetic declination was determined to be 15° 30' E.

Dependent Resurvey of the South Boundary, T. 23 S., R. 61 E.

Reestablishment of the Survey Executed by
Deputy Surveyors Brunt and Proctor in 1881.

From the cor. of Ts. 23 and 24 S., Rs. 61 and 62 E., which is monumented with an iron post, 3 ins. diam., firmly set in a mound of stone, 6 ft. diam., 3 ft. high, mkd. and witnessed as described in the official record.

From this cor., the cor. of secs. 19, 24, 25 and 30, which is monumented with a basalt stone, 16 x 14 x 12 ins., firmly set in a mound of stone, mkd. and witnessed as described in the official record, bears N. 0° 10' W., 159.60 chs. dist.

At this corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T23S
R61E R62E
S24|S19
S25|S30
1956

Bury the cor. stone alongside the iron post.

Raise a mound of stone, 4 ft. base, 3 ft. high, W. of cor.

S. 89° 44' W., along the S. bdy. of sec. 36.

Over nearly level land, through scattered greasewood and cacti.

Desc. 23 ft. over W. slope.

4.00 Wash, 1.50 chs. wide, 10 ft. deep, drains NW.; continue descent; desc. 34 ft. over gradual WNW. slope.

27.17 Wash, 1 ch. wide, 2 ft. deep, drains N.; asc. 21 ft. over E. slope.

28.65 Top of low spur, slopes NE.

29.65 Gulch, 60 lks. wide, drains NE.; asc. 178 ft. over E. slope.

40.31 Point for the ¼ sec. cor. of secs. 1 and 36, which is monumented with a basalt stone, 10 ins. above ground, mkd. and witnessed as described in the official record.

At the corner point

Set an iron post, 30 ins. long, 2½ ins. diam., 6 ins. in the ground to solid rock, with brass cap mkd.

1/4 S36
S 1
1956

Bury the basalt stone alongside the iron post and raise a mound of stone, 4 ft. diam., 2 ft. high, around the cor.