

342

Dependent Resurvey of the South Boundary, T. 22 S., R. 58 E.

Chains	
	T22S R58E S31 S32 S6 S5 T23S 1956
	from which
	A pine, 8 ins. diam., bears N. 71° 15' E., 61 lks. dist., mkd. T22S R58E S32 BT.
	A pine, 9 ins. diam., bears S. 38° 00' E., 16 lks. dist., mkd. T23S R58E S5 BT.
	A pine, 6 ins. diam., bears S. 56° 15' W., 32 lks. dist., mkd. T23S R58E S6 BT.
	A pine, 10 ins. diam., bears N. 49° 00' W., 58 lks. dist., mkd. T22S R58E S31 BT.
	Land, rough mountainous. Soil, sandy and gravelly loam. Timber, pine, and juniper. Undergrowth, sagebrush.
	S. 88° 48' W., bet. secs. 6 and 31. (Distance measured.)
	Over heavily rolling land, through heavy timber; asc. 42 ft. over E. slope.
1.00	Trail, bears NE. and SW., on top of low spur, slopes NE.; desc. 50 ft. over W. slope.
7.00	Wash, 30 lks. wide, 3 ft. deep, drains NE.; asc. 60 ft. over NNE. slope.
11.00	Top of ascent; slopes NNE.; desc. 50 ft. over NW. slope.
25.00	Wash, 40 lks. wide, 2 ft. deep, drains NE.; asc. 180 ft. over NE. slope.
37.30	Top of ascent, slopes N.; desc. 35 ft. to the cor.
42.06	Point for the ¼ sec. cor. of secs. 6 and 31, at proportionate dist.; there is no remaining evidence of the original cor.
	Set an iron post, 30 ins. long, 2½ ins. diam., 20 ins. in the ground, with brass cap mkd.
	½ S31 S 6 1956
	from which
	A pine, 10 ins. diam., bears N. 35° 45' E., 44 lks. dist., mkd. ½ S31 BT.
	A pine, 12 ins. diam., bears S. 34° 35' W., 23 lks. dist., mkd. ½ S6 BT.
	Raise a mound of stone, 4 ft. base, 2 ft. high, N. of cor.
	Cont. over heavily rolling land, through heavy timber.
45.10	Wash, 1.00 ch. wide, 2 ft. deep, drains NE.; asc. 25 ft. over NNE. slope.