

Dependent Resurvey of a the Subdivisional Lines

T. 22 S., R. 58 E.

Chains

Land, rolling, mountainous.
Soil, sandy and gravelly loam.
Timber, pinion, pine and juniper.
Undergrowth, cactus and sagebrush.

Subdivision of Section 20, T. 22 S., R. 58 E.

From the $\frac{1}{4}$ sec. cor. of secs. 20 and 29, hereinbefore described.

N. $1^{\circ} 18'$ E., on the North-South Center line of sec. 20 along the E. side of a graded road.

Over rolling land, through medium heavy timber and undergrowth.

Asc. 38 ft. over S. slope.

4.63 Top of low spur, slopes NW.; desc. 11 ft. over N. slope.

6.30 Bottom of descent; begin ascent; asc. 52 ft. over S. slope.

20.58 Point for the Center-South $\frac{1}{16}$ sec. cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 8 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T22S R58E

C

S $\frac{1}{16}$ | S 20

C

1957

21.50 Wash, 30 lks. wide, 6 ft. deep, drains SW.; asc. 50 ft. over S. slope.

25.00 Top of spur, slopes W.

35.50 Wash, 30 lks. wide, 8 ft. deep, drains W.

39.00 Graded road, 1 ch. W., bears W. and S. $1^{\circ} 18'$ E.

41.16 Intersect the East-West Center line.

Point for the Center $\frac{1}{4}$ sec. cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.

T22S R58E

C $\frac{1}{4}$ | S20

1957

Raise a mound of stone, 4 ft. base, $2\frac{1}{2}$ ft. high, W. of cor.

Cont. over rolling land, through scattered timber; asc. 51 ft. over gradual WSW. slope.

50.30 Wash, 50 lks. wide, 6 ft. deep, drains W.; asc. 216 ft. over steep S. slope.

61.74 Point for the Center-North $\frac{1}{16}$ sec. cor.

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.