

DEPENDENT RESURVEY OF A PORTION OF THE SOUTH BOUNDARY, T. 19 N., R. 20 E.,
M. D. M., NEVADA

Chains

Reestablishment of the Survey Executed by
J. S. Lawson, Deputy Surveyor, in 1861.

The cor. of secs. 2, 3, 34 and 35, Ts. 18 and 19 N., R. 20 E. is marked by an old mound of stone. This point in relation to other corners is as shown on plat of a survey of the private lands in secs. 3, 33 and 34 and is accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 10 ins. in the ground, and in a mound of stone to top, with brass cap mkd.

T 19 N R 20 E

S 34	S 35
S 3	S 2
T 18 N	

1956

S. $88^{\circ}45'$ W., bet. secs. 3 and 34.

Descend 380 ft. over general W. slope, changing to SW. slope.

19.93

The E $\frac{1}{16}$ of secs. 3 and 34, monumented by an iron pipe, $\frac{3}{4}$ ins. in diam., 24 ins. long, firmly set in the ground and surrounded by a mound of stone.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 15 ins. in the ground, with the $\frac{3}{4}$ ins. iron pipe alongside and in a mound of stone to top, with brass cap mkd.

T 19 N R 20 E

E $\frac{1}{16}$	S 34
	S 3
T 18 N	

1956

Descend 160 ft. over SW. slope.

39.86

The $\frac{1}{4}$ sec. cor. of secs. 3 and 34 is marked by an iron pipe $\frac{3}{4}$ ins. diam., 30 ins. long, firmly set in the ground, and surrounded by a mound of stone. This point is accepted as the best existing evidence of the position of the original corner.

At the corner point

Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 17 ins. in the ground, with the $\frac{3}{4}$ ins. iron pipe alongside and in a mound of stone to top, with brass cap mkd.

T 19 N R 20 E

$\frac{1}{4}$	S 34
	S 3
T 18 N	

1956