

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISION OF T. 19 N., R. 20 E.

Chains 34.00	Wash, course NW.
34.54	Fence bears NE. and SW. 0.22 chs. to fence corner from which fences bear W. and SW.
35.00	Leave valley; ascend 40 ft. over rocky NE. slope.
38.88	The $\frac{1}{4}$ sec. cor. of secs. 27 and 34 marked by an old imbedded mound of stone over which a larger mound of stone has been built. This point is accepted as the best existing evidence of the position of the original corner. At the cor. point in the center of the old mound of stone Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 20 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T 19 N R 20 E $\frac{1}{4} \quad \frac{S 27}{S 34}$ 1956 N. $88^{\circ}34'$ W., beginning new measurement. Ascend 230 ft. over NE. slope.
11.00	Shoulder, projects N. 1.50 chs. to knoll; descend 40 ft. over NW. slope.
12.50	Swale, drains N.; ascend 20 ft. over NE. slope.
20.02	Point for the W $\frac{1}{16}$ sec. cor. of secs. 27 and 34. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, and in a mound of stone to top, with brass cap mkd. T 19 N R 20 E W $\frac{1}{16}$ $\frac{S 27}{S 34}$ 1956 Ascend 20 ft. over NE. slope.
25.00	Ridge, bears SE. and NW.; descend 250 ft. over steep, rocky SW. slope.
40.04	The cor. of secs. 27, 28, 33 and 34. Land, mountainous, and slightly rolling. Soil, rocky. No timber.
	SUBDIVISION OF SECTION 34, T. 19 N., R. 20 E., M.D.M., NEVADA
	From the $\frac{1}{4}$ sec. cor. of secs. 3 and 34 on the S. bdy. of the Tp. N. $2^{\circ}52'$ W., on the N. and S. center line of sec. 34. Ascend 35 ft. over gentle SW. slope.