

Dependent Resurvey of the South Boundary of T. 13 S., R. 47 E.

Chains

40.00

The original $\frac{1}{4}$ sec. cor. of secs. 6 and 31, which is mkd. by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for sec. 31 only. I alter the markings on the brass cap to read

T13S R47E

 $\frac{1}{4}$ S31

57

1921

I repair and enlarge the auxiliary mound of stone.

78.38

The original cor. of Ts. 13 and 14 S., Rs. 46 and 47 E., which is mkd. by an iron post, 3 ins. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for the SW. cor. of sec. 31, T. 13 S., R. 47 E. only. I alter the markings on the brass cap to read

T13S

R46E | R47E

S31

T14S

R46E

S10

57

1921

I repair and enlarge the auxiliary mound of stone.

Land, nearly level.

Soil, sandy and gravelly loam.

Timber, none; undergrowth, creosote bush.

Dependent Resurvey of the East Boundary of T. 13 S., R. 47 E.

Reestablishment of the survey executed by H. Good, U. S. Transitman, in 1921.

Note: For the topography along this boundary, see the record of the 1921 independent resurvey of the east boundary of T. 13 S., R. 47 E.

From the SE. cor. of sec. 36, T. 13 S., R. 47 E. only, which is mkd. by an iron post, 3 ins. diam., hereinbefore described.

North, along the E. bdy. of sec. 36.

Over nearly level land, through scattered undergrowth.

40.00

The original $\frac{1}{4}$ sec. cor. of secs. 31 and 36, which is mkd. by an iron post, 1 in. diam., firmly set, mkd. and witnessed as described in the official record. This cor. now functions for sec. 36 only. I alter the markings on the brass cap to read

T13S

R47E

S36

57

1921

I repair and enlarge the auxiliary mound of stone.