

Survey of the West Boundary of T. 15 S., R. 49 E.

Chains

57.75

Wash, 20 lks. wide, 1 ft. deep, drains SW.

80.00

Point for the cor. of secs. 7, 12, 13 and 18.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S
R48E R49E
S12 | S 7
S13 | S18
1957

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Land, nearly level.

Soil, sandy and volcanic ash.

Timber, none; undergrowth, sagebrush and creosote bush.

North, bet. secs. 7 and 12.

Over nearly level land, through heavy undergrowth.

40.00

Point for the ¼ sec. cor. of secs. 7 and 12.

Set an iron post, 36 ins. long, 1 in. diam., 30 ins. in the ground, with brass cap mkd.

T15S
R48E R49E
¼
S12 | S 7
1957

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

77.40

Oiled road, U. S. Highway No. 95, bears N. 73° W. and S. 73° E.

80.00

Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S
R48E R49E
S 1 | S 6
S12 | S 7
1957

Raise a mound of stone, 3 ft. base, 2 ft. high, W. of cor.

Land, nearly level.

Soil, sandy and volcanic ash.

Timber, none; undergrowth, creosote bush and sagebrush.

North, bet. secs. 1 and 6.

Over nearly level land, through heavy undergrowth.

.85

Telephone line, bears N. 73° 10' W. and S. 73° 10' E.