

Dependent Resurvey of the North Boundary, T. 16 S., R. 50 E.

Chains	
42.04	Point for the $\frac{1}{4}$ sec. cor. of sec. 31 only, at record distance. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T15S R50E $\frac{1}{4}$ S 31 <hr/> T16S 1957 Deposit broken glass around the post, 12 ins. below the surface of the ground.
52.50	Wash, 20 lks. wide, 2 ft. deep, drains S.
61.60	Wash, 30 lks. wide, 4 ft. deep, drains S.
66.20	Wash, 10 lks. wide, 2 ft. deep, drains S.
73.50	Wash, 10 lks. wide, 1 ft. deep, drains S.
81.81	The cor. of Ts. 15 and 16 S., Rs. 49 and 50 E., which is mkd. by an iron post, 3 ins. diam., 6 ins. above ground, firmly set, mkd. and witnessed as described in the 1921 survey record. Land, nearly level. Soil, sandy and gravelly clay loam. Timber, none; undergrowth, creosote bush and greasewood.

Survey of a Portion of the West Boundary of T. 15 S., R. 50 E.

	From the cor. of secs. 7, 12, 13 and 18, Ts. 15 S., Rs. 49 and 50 E., which is mkd. by an iron post, 2 ins. diam., 8 ins. above ground, firmly set, mkd. and witnessed as described in the 1942 survey record. North, bet. secs. 7 and 12. Over nearly level land, through heavy undergrowth.
40.00	Point for the $\frac{1}{4}$ sec. cor. of secs. 7 and 12. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd. T15S R49E R50E $\frac{1}{4}$ S12 S 7 1957 Raise a mound of stone, 3 ft. base, $1\frac{1}{2}$ ft. high, W. of cor.
80.00	Point for the cor. of secs. 1, 6, 7 and 12. Set an iron post, 30 ins. long, $2\frac{1}{2}$ ins. diam., 24 ins. in the ground, with brass cap mkd.