

119

Survey of the East Boundary of T. 15 S., R. 50 E.

Chains

Set an iron post, 36 ins. long, 1 in. diam., 12 ins. in the ground to solid rock, and in a mound of stone to top, with brass cap mkd.

T15S
R50E R51E
 $\frac{1}{4}$
S12 | S 7
1957

Continue over gently rolling land; asc. 51 ft. over gradual SSE. slope.

80.00

Point for the cor. of secs. 1, 6, 7 and 12.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S
R50E R51E
 $\frac{1}{4}$
S 1 | S 6
S12 | S 7
1957

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Land, south half mountainous, north half nearly level to gently rolling.

Soil, sandy and gravelly loam.

Timber, none; undergrowth, creosote bush, sagebrush, and shadscale.

North, bet. secs. 1 and 6.

Over gently rolling land, through heavy undergrowth; asc. 126 ft. over S. slope.

26.00

Top of low ridge, bears NE. and SW.; desc. 46 ft. over N. slope.

37.50

Wash, 30 lks. wide, 6 ft. deep, drains NW.

40.00

Point for the ¼ sec. cor. of secs. 1 and 6.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

T15S
R50E R51E
 $\frac{1}{4}$
S 1 | S 6
1957

Raise a mound of stone, 3 ft. base, 1½ ft. high, W. of cor.

Continue descent; desc. 69 ft. over NW. slope.

56.00

Wash, 20 lks. wide, 2 ft. deep, drains W.; continue over nearly level land.

80.00

Point for the cor. of Ts. 14 and 15 S., Rs. 50 and 51 E.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.