

## Dependent Resurvey of a Portion of the S. Bdy., T. 44 N., R. 33 E.

Chains

Reestablishment of the survey executed by G. W. Garthside and C. L. Preble in 1873.

Beginning at the cor. of Tps. 43 and 44 N., Rs. 33 and 34 E., monumented with an iron post, set, mkd. and witnessed as described in the field notes of T. 44 N., R. 34 E., surveyed concurrently under this same group.

West, bet. secs. 1 and 36.

Desc. 80 ft. over NW. slope, through scattered sagebrush.

12.00 Over nearly level land, through thick sagebrush.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 1 and 36, at record dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T44N R33E  
 $\frac{1}{4}$   $\frac{S36}{S 1}$   
1958

80.00 Point for the cor. of secs. 1, 2, 35 and 36, at record dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T44N R33E  
 $\frac{S35}{S 2}$  |  $\frac{S36}{S 1}$   
T43N R33E  
1958

Land, nearly level, except small hill on E. side.

Soil, sandy loam, except on hill.

Vegetation, sagebrush and scattered June grass.

West, bet. secs. 2 and 35.

Over nearly level land.

40.00 Point for the  $\frac{1}{4}$  sec. cor. of secs. 2 and 35, at record dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

T44N R33E  
 $\frac{1}{4}$   $\frac{S35}{S 2}$   
T43N R33E  
1958

58.18 Unimproved road, bears N. and S.

80.00 Point for the cor. of secs. 2, 3, 34 and 35, at record dist.; there is no remaining evidence of the original cor.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.