

Dependent Resurvey of a portion of the S. Bdy., T. 46 N., R. 33 E.

Chains	(9th Standard Parallel North)
17.61	Dry wash, 15 lks. wide, drains N. 60° E.
40.24	<p>The standard <math>\frac{1}{4}</math> sec. cor. of sec. 33, mkd. by a stone 12 x 10 x 8 ins. firmly set in small mound of stone.</p> <p>At the cor. point,</p> <p>Set an iron post 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>S C T46N R33E <u><math>\frac{1}{4}</math> S33</u> 1958</div> <p>Bury old cornerstone alongside iron post.</p> <hr/> <p>N. 89° 10' W., beg. new measurement.</p>
40.64	<p>The standard cor. of secs. 32 and 33, mkd. by a stone 30 x 15 x 8 ins. firmly set in large mound of stone, with faint grooves on E. and W. faces.</p> <p>At the cor. point,</p> <p>Set an iron post 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 15 ins. in the ground, and in mound of stone to top, with brass cap mkd.</p> <div>S C T46N R33E <u>S32   S33</u> 1958</div> <p>Bury old cornerstone alongside iron post.</p> <p>Land, gradual E. slope. Soil, sandy loam. Vegetation, thick sagebrush.</p> <hr/>
Dependent Resurvey of a Portion of the Subdivision, T. 46 N., R. 33 E.	
40.40	<p>Reestablishment of the survey executed by G. W. Garthside and C. L. Preble in 1874.</p> <p>From the cor. of secs. 1, 2, 35 and 36, on the S. bdy. of the Tp.</p> <p>N. 0° 10' W., bet. secs. 35 and 36.</p> <p>Over level land, through thick sagebrush.</p> <p>Point for the <math>\frac{1}{4}</math> sec. cor. of secs. 35 and 36, at proportionate dist.; there is no remaining evidence of the original cor.</p> <p>Set an iron post 30 ins. long, <math>2\frac{1}{2}</math> ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div>T46N R33E <math>\frac{1}{4}</math> S35   S36 1958</div>
80.80	<p>Point for the cor. of secs. 25, 26, 35 and 36, at proportionate dist; there is no remaining evidence of the original cor.</p>