

## Dependent Resurvey of a Portion of the Subdivision, T. 22 S., R. 63 E.

## Chains

39.990

The  $\frac{1}{2}$  sec. cor. of secs. 26 and 27, which is mkd. by an iron post, 1 in. diam., firmly set in the ground, mkd. and witnessed as defined in the 1931, resurvey record.

Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.

from which

Point for reference monument bears N.  $45^{\circ}$  E., 45.4 lks. (30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor.

Point for reference monument bears N.  $45^{\circ}$  W., 45.4 lks. (30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor.

## Dependent Resurvey of a Portion of the South Boundary, T. 22 S., R. 63 E.

Resurvey of surveys executed by C. A. Magee in 1883 and independently resurveyed by Swanholm and Yundt in 1931, with the reestablishment of the resurvey made by Swanholm and Yundt in 1931.

From the cor. of secs. 2, 3, 34 and 35, hereinbefore described.

S.  $89^{\circ} 49'$  W., bet. secs. 3 and 34.

Over gently rolling flood plain, through moderately heavy undergrowth.

0.98

Power line, 5 strands on steel frames, bears NW. and SE.

10.01

Point for the East-East  $\frac{1}{64}$  sec. cor. of secs. 3 and 34, at proportionate dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

E E  $\frac{1}{64}$   
 $\frac{S34}{S 3}$   
 1957

Deposit broken glass 12 ins. below the surface of the ground and raise a collar of stone around the iron post.

10.70

Old road from Las Vegas to Boulder City and Searchlight, bears N. and S.

14.76

Los Angeles and Salt Lake Railroad (Boulder branch), bears N.  $63^{\circ} 58'$  W. and S.  $63^{\circ} 58'$  E.

16.58

Western Union telegraph line, bears N.  $63^{\circ} 58'$  W. and S.  $63^{\circ} 58'$  E.

20.02

Point for the East  $\frac{1}{16}$  sec. cor. of secs. 3 and 34, at proportionate dist.

Set an iron post, 30 ins. long,  $2\frac{1}{2}$  ins. diam., 24 ins. in the ground, with brass cap mkd.

E  $\frac{1}{16}$   
 $\frac{S34}{S 3}$   
 1957

Deposit broken glass 12 ins. below the surface of the ground and raise a collar of stone around the iron post.