

Dependent Resurvey of a Portion of the South Boundary, T. 22 S., R. 63 E.

Chains

from which

Point for reference monument bears N. 45° E., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor.

Point for reference monument bears N. 45° W., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957; and an arrow pointing to the cor.

70.055 Point for the West-West 1/64 sec. cor. of secs. 3 and 34, at proportionate dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.

W W 1/64

 S 3
 1957

Deposit broken glass 12 ins. below the surface of the ground and raise a collar of stone around the iron post.

80.060 The cor. of secs. 3, 4, 33 and 34, which is mkd. by an iron post, 2 ins. diam., firmly set, mkd. and witnessed as defined in the 1931 resurvey record.

Rebuild mound of stone, 3 ft. base, 2 ft. high, W. of cor.

from which

Point for reference monument bears N. 45° E., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor.

Point for reference monument bears N. 45° W., 45.4 lks.(30 ft.) dist. Set a 1 in. T-iron stake, 24 ins. long, 14 ins. in the ground, with a cadmium plated cap mkd. U. S. Bureau of Land Management Survey Corner RM 30 ft. 1957, and an arrow pointing to the cor.

Land, gently rolling.

Soil, sandy clay loam.

Timber, none.

Undergrowth, creosote bush and sagebrush.

Dependent Resurvey, Portion of Subdivision, T. 22 S., R. 63 E.

Resurvey of surveys executed by C. A. Magee in 1883, and independently resurveyed by Swanholm and Yundt in 1931, with the reestablishment of the resurvey made by Swanholm and Yundt in 1931.

From the cor. of secs. 3, 4, 33 and 34 on the S. bdy. of the township.

N. 0° 09' E., bet. secs. 33 and 34.

Over slightly rolling bench land, through medium dense undergrowth.

Desc. 95 ft. over gradual NNW. slope.

9.999 Point for the South-South 1/64 sec. cor. of secs. 33 and 34, at proportionate dist.

Set an iron post, 30 ins. long, 2½ ins. diam., 24 ins. in the ground, with brass cap mkd.